

桶內吸油濾網 Suction Filter

SFA系列過濾器是用於液壓或潤滑系統的吸油泵浦入口管路上，安裝時要浸沒在油箱油液中，最大流量可達900 l/min (該流量是在油液黏度 30 mm²/s 時測得)。

用於保護液壓泵及其他油壓零組件，避免吸入因製造、維修或在替系統加油時所產生的顆粒污染物造成損害，並能延長系統元件的使用壽命，減少停機次數。

SFA series filters are suitable for use in the suction line, submerged in the reservoir. They are available for nominal flows up to 900 l/min (with oil at 30 mm²/s). The SFA series are suitable to protect the hydraulic pump and other oil pressure spare part.

特點：

- 1.上下蓋與濾網採膠合方式製作，濾網完全不變形，達到100%過濾效果。
- 2.較大過濾面積，延長清洗更換週期。
- 3.接頭與上蓋一體成型，絕不斷裂。
- 4.專利上下蓋卡榫設計，絕不脫落。
- 5.中管採用高強度工程塑膠材質，提供強韌支撐。
- 6.提供多種尺寸、過濾精度濾網。

材質：

上下封蓋：高強度，耐油耐腐蝕工程塑膠
支撐中管：高強度，耐油耐腐蝕工程塑膠
濾網：不鏽鋼，100 Mesh

Characterization：

- 1.Elements glue to caps tightly, enhanced efficiency of filtrating.
- 2.Larger filtering area extends replacement cycle.
- 3.Caps shaped with connections, not likely cracking.
- 4.Patent design of locked caps, not likely came off.
- 5.Support tube by Nylon provides strong support.
- 6.Provide plenty of sizes and elements.

Material：

Connections & End cap：Nylon
Support tube：Nylon
Element material：Stainless Steel, 100 Mesh



► 安裝尺寸及外型尺寸 (Mounting size)

型式編號 (Model code)		A	φ D	H	CH	過濾精度(Filtration accuracy)
Type	Model	PT	mm	mm	mm	Mesh
SFA	012	1/2"	60	142	40	100
	034	3/4"	60	142	40	100
	100	1"	70	187	50	100
	114	1-1/4"	70	187	50	100

► 型號說明 (Model code)

SFA	012	100M
------------	------------	-------------

接續螺紋規格 (Connection threaded specification) — 濾蕊規格 (Filter element)

